CZ Patch Library QuickStart

1) Connect MIDI cables:

CZPL CASIO OUT -----> Synthesizer MIDI IN CZPL CASIO IN -----> Synthesizer MIDI OUT

2) Power the device with either:

5V USB adapter with the included cord

- OR -

9V, center+ adapter.

After a few seconds, the display should display PrSt, indicating preset mode. Press the D (Enter) key on the CZPL to enter Preset mode.

Load a Preset

1) Switch your Casio to Internal 1 (CZ-101/CZ-1000) or Memory Location A1 (CZ-3K/5K/CZ-1)

2) Enter a number between 0 and 2185 with the numeric keypad.

2) Press D to send that preset to Memory Location A1.

3) You can use the # and * buttons to go up or down by one and send to the CZ automatically.

Save a User Patch

- 1) Press C (Write) to enter Save Mode.
- 2) Put the patch that you want to save into Casio Memory Location A1. You could either write a patch here from a different location on the Casio, or load one of the presets from the CZPL.
- 3) Enter a number between 0000 and 9999 with the keypad, or the */# buttons.
- 4) Press D (Enter) to save the patch to your chosen location.

Load a User Patch

- 1) Press A to enter Main Menu mode.
- 2) Press 2 to select User mode, then press D (Enter) to enter user mode.
- 3) Using the numeric keypad or */# buttons, choose the patch you want to load.
- 4) Press D (Enter) to load the patch to Casio Memory Location A1.

More information:

Download full manual and preset list at: https://lewismidi.com/czpl

Main Menu	Description
1 - PrSt	Load Presets
2 - USEr	Load/Save User Patches
3 - bAnk	Load/Save Banks
4 - Arpg	Use Arpeggiator
5 - rAnD	Load Random Presets
6 - SELF	Play Random Melodies
7 - SEtt	Adjust Settings
MOdL	Set Casio Model
CLOC	Internal/External Clock select
Atrg	Arpeggio trigger source
ChAn	Arpeggio MIDI Channel
SPLT	Arpeggio keyboard split
LtCh	Arpeggio Latch Mode
BnCh	External Bank Change

Preset Category	Start #
Bass	0
Brass	158
Drums	218
FX	368
Guitar	621
Keys	680
Strings	994
Synth	1149
Tuned Perc.	1711
Unclassified	1853
Voice	2005
Winds	2040

